D 40/2.7

DEPENDABLE AMF/HOMKO LAWN MOWERS

D40 13

RECEIVED
SEPT. 15, 1966 9-15-66
FROM HARDWARE AGE P. 19
INSERT

the quality line with the big extras

A.

GRASS CATCHER KIT

High density polyethylene transition with newly designed uplift action to speed flow of grass to back of bag. Optional on Models 1219, 1220, 1221, 1212.





BIG EXTRA DIPLOMAT FEATURES

1. Instant One Lever Cutting Height Adjustment
2. Stainless Steel Flexible-tipped Flexor Blade
3. Stand-up Safety Starting Behind Mower

DIPLOMAT Model 1221

22-INCH 3½ H.P.
Self-propelled Rotary with Stainless Steel Flexor Blade

The finest all-around rotary. All the latest safety and convenience features. Grass catcher optional.

Design — Monorail holds housing in quadramatic suspension. All steel deck. **Blade**—Stainless steel Flexor Blade. Flexible tips absorb shock. Guaranteed against crankshaft damage for life of mower.* **Engine**—Powerful 4-cycle engine, built to rigid AMF specifications. Quietone muffler. **Stand-up Safety Starting**—Easy-pull recoil start with rope mounted on handle. **Controls**—Throttle and clutch controls on handle. **Handle**—Adjustable to 3 heights for mowing, straight-up for storage. **Drive**—Positive action front wheel gear drive. **Cutting Heights** — Single lever adjusts from 1″ to 3″ instantly, with one hand. **Grass Catcher Kit**—Available as accessory No. 5537. **Shipping Weight**—88 lbs.

DIPLOMAT

Model 1220—22-INCH 3½ H.P.
Model 1219—19-INCH 3 H.P.
Free Wheeling Rotary with Stainless Steel Flexor Blade

A fast, smooth, powerful mower that's easy to maneuver. Has many outstanding quality features.

Design — Monorail holds housing in quadramatic suspension. All steel deck. **Blade**—Stainless steel Flexor Blade. Flexible tips absorb shock. Guaranteed against crankshaft damage for life of mower.* **Engine**—Powerful 4-cycle engine, built to rigid AMF specifications. Quietone muffler **Stand-up Safety Starting**—Easy-pull recoil start with rope mounted on handle. **Controls**—Jet knob single lever stand-up control on handle. Choke-o-Matic throttle. **Handle**—Adjustable to 3 heights for mowing, straight-up position for storage. **Cutting Heights**—Single lever adjusts from 1″ to 3″ instantly, with one hand. **Grass Catcher Kit**—Available as accessory No. 5537. **Shipping Weight**—Model 1220, 72 lbs.; Model 1219, 65 lbs.

FALCON Model 1232

22-INCH 3½ H.P. 2-speed Self-propelled Rotary with Stainless Steel Flexor Blade

This efficient double duty mower with front wheel gear drive gets hard work done fast. Here's the answer for difficult lawns—easy two-speed mowing.

2-Speed Front Wheel Drive—High for normal jobs, low for heavy duty mowing. **Blade**—Stainless steel Flexor Blade.* **Engine** — 3½ H.P. 4-cycle engine, built to rigid AMF specifications. Quietone muffler. Easy oil fill. **Safety Start**—Easy-pull starter rope on handle. **Controls** — Jet knob stand-up controls. Choke-o-Matic throttle, clutch. **Handle**—Self-storage. **Grass Discharge**—Side discharge chute. **Cutting Heights** — Selector cutting height adjustment at each wheel, ⅞″ to 3⅛″. **Wheels** — White sidewall steel. Tires, 9¼″ front; 8″ diamond tread rear. **Grass Catcher Kit** — Available as accessory No. 5529. **Shipping Weight**—104 lbs.

All AMF/Homko mowers meet all A.S.A. safety standards.

DIPLOMAT
High-wheeler
Model 1212

22-INCH 3½ H.P. Self-propelled Heavy Duty Rotary Lawn and Weed Mower with Exclusive Flexor Blade

A lawn mower and a weed mower in one! Big bicycle type wheels let it go in anywhere—fields, roadways, wherever grass and weeds need mowing. Loaded with power, handles beautifully.

Design—Trimmer type housing. All steel deck. **Blade**—High tempered steel Flexor Blade.* **Engine**—Powerful 4-cycle engine, built to rigid AMF specifications. Quietone muffler. Handy top-of-engine oil fill. **Starting** — Safety start with rope on handle. **Controls** — Jet knob stand-up throttle and clutch controls on handle. **Drive** — Positive action front wheel gear drive. **Grass Discharge** — Powerful tornado action from side discharge. **Cutting Heights**—Adjustable from 1″ to 3″ instantly, with one hand. Single lever adjusts all 4 wheels at once. **Wheels**—Rear, 20″ chrome, bicycle type. Sealed ball bearings. Pneumatic tires. Front, all steel, 8 x 1.75 diamond tread tires. **Grass Catcher Kit**—Available as accessory No. 5537. **Shipping Weight**—108 lbs.

*WE UNCONDITIONALLY GUARANTEE every mower originally equipped with our 3-piece flexible blade against a bent engine crankshaft. In case of a bent crankshaft the entire mower, including the blade and all clutch parts, must be returned intact to the Factory, where it will be repaired and returned to the customer with NO CHARGE for labor, parts or freight.

FURY Model 1240

22-INCH 3½ H.P. Deluxe Free Wheeling Rotary with Flexor Blade

This rugged mower with staggered wheel design trims close to trees and fences, does a fine all-around mowing job. Fast, smooth, powerful, and built to last.

Blade—Exclusive Flexor Blade.* **Engine**—3½ H.P. 4-cycle engine built to rigid AMF specifications. Quietone muffler. Easy oil fill. **Starter**—Upright pull-through. **Controls**—Jet knob controls. Choke-o-Matic throttle on handle gives stand-up control of engine. **Handle**—Self-storage. **Grass Discharge**—Staggered wheel front side discharge chute. Front corner and rear baffle for cleaner grass discharge; helps prevent clogging. **Cutting Heights**—Quick wheel adjustment. No bolts. Simply move lever to selected cutting height, from 1¼" to 3¼". **Wheels**—8" steel with ribbed tread tires, pre-lubricated oilite type bearings. **Shipping Weight**—73 lbs.

VALIANT Model 1224

22-INCH 3½ H.P. Free Wheeling Rotary with Flexor Blade

Lots of mower for the least money! Easy to start with upright pull-through starter. Easy to operate with controls on the handle. A neat, dependable performer.

Design—Staggered wheel design. **Blade**—High tempered steel Flexor Blade.* **Engine**—3½ H.P. 4-cycle engine built to rigid AMF specifications. **Starter**—Upright pull-through. **Controls**—Choke-o-Matic throttle on handle gives stand-up control of choke, stop and blade speeds. **Handle**—Tubular steel, self-storage. Vinyl handle grips. **Grass Discharge**—Front discharge chute. Deck contour gives cleaner grass discharge, helps prevent clogging. **Cutting Heights**—Adjustable from 1¼" to 2¾". **Wheels**—8" steel with ribbed tread tires, pre-lubricated oilite type bearings.

Shipping Weight—70 lbs.

MOW-TRAC RIDER FEATURES

1. Big Extra: Orbit Disc Power Drive eliminates troublesome gears.

2. Big Extra: Change cutting height while mowing by single lever adjustment.

3. Big Extra: Jet stick controls are conveniently located on console panel.

4. Big Extra: Rear bumper doubles as storage stand, includes hitch for accessories.









RIDER ACCESSORIES

Model 5548—Seat Back
Model 29377—Seat Cushion



40" Snow Blade and Tire Chain Kit
#5451—For Model 1266
#5453—For Models 1262, 1265

Model 5616—Lawn Sweeper and Sweeper Hitch

AMF/HOMKO RIDERS will accommodate all standard accessories made by other manufacturers, such as lawn rollers, utility carts, seeder and fertilizer spreaders.

MOW-TRAC SUPER 30 Model 1266

30-INCH 7 H.P. Riding Rotary Mower

Big power in a big job mower. Mow up to an acre an hour, climbing slopes, zipping easily around trees. Pull carts, add snow blade accessory to plow snow.

Design—Trimmer type housing. Heavy gauge steel frame. Draw bar hitch. Stores on end. **Blade**—30" austempered steel high lift. **Engine** — 4-cycle engine, built to rigid AMF specifications. Muffler guard. Automotive type differential. Easy-pull recoil starter. **Controls**—Jet stick control of choke, 4 speeds forward, neutral and reverse. Combination clutch and brake pedal. Blade throw-out lever stop blade quickly. **Orbit Disc Power Drive**—Clutched for extra smooth starting. **Belt-Driven Quill**—Anti-shock Timken bearing quill. **Cutting Heights**—Adjust while mowing, from 1½" to 4". Nonmarking low profile pneumatic tires. **Shipping Weight**—354 lbs.

Deluxe Self-propelled Reel

MARKSMAN Model 1115 21-INCH 2½ H.P.
CHAMPION Model 1105 18-INCH 2½ H.P.

Grass Catcher Standard Equipment on Models 1115 and 1105

Design—Heavy steel box-type construction. **Blades**—Austempered steel precision cutting blades. Ball bearings on reel shaft lubricated for life. **Engine**—2½ H.P. 4-cycle engine, built to rigid AMF specifications. Quietone muffler. Easy-pull start. **Controls**—Jet knob controls. Choke-o-Matic throttle on handle controls choke, stop and reel speeds. **Handle**—Lift-o-Matic. Raise to move forward, lower to stop. Returns automatically to "off" position. Stands up for storage. **Cutting Heights**—½" to 2¼". Low or medium recommended for best mowing. **3-Point Cutter Bar Adjustment**—Center cutter bar adjustment decreases costly sharpening. **Roller**—3-piece. Plastic coated for quieter operation. **Shipping Weight**—Model 1115, 97 lbs.; 1105, 91 lbs.

TILLERS

DELUXE SELF-PROPELLED REVERSING ROTARY

Vertical Shaft	Horizontal Shaft
Model 1347—28-INCH 5 H.P.	Model 1349—28-INCH 5 H.P.
Model 1346—26-INCH 4 H.P.	Model 1348—26-INCH 4 H.P.
Model 1345—26-INCH 3½ H.P.	

STANDARD SELF-PROPELLED REVERSING ROTARY

Model 1344—22-INCH 3 H.P.

Engine—4-cycle, built to rigid AMF specifications. Easy-pull recoil starter. **Controls**—Till-a-Matic drive control on handle. Remote control of Choke-o-Matic throttle. **Exclusive Ultragear Transmission**—Extra heavy duty, with manganese bronze gear and microfinish worm, Timken bearings. Performance-proved gear box. **Direct Belt Drive**—No clutch adjustments. **Reverse-Safety Control**—Stops tiller. **Tilling Depth Control**—Handle adjustable for height. **Tines**—Shielded bolo type 14" dia. **Construction**—Heavy gauge, reinforced steel. 10" heavy duty transport wheels. **Accessories**—Pic Tine Kit; Furrow Opener; Bolo Type Tine Extension Kit. **Shipping Weight**—Model 1347, 162 lbs.; 1346, 152 lbs.; 1345, 142 lbs.; 1344, 130 lbs.; 1349, 162 lbs.; 1348, 152 lbs.

MOW-TRAC HI-BAR 30 Model 1265
30-INCH 6 H.P. Riding Rotary Mower

MOW-TRAC HI-BAR 26 Model 1262
26-INCH 5 H.P. Riding Rotary Mower

Two classy riders engineered for power performance. Mow safely on slopes, maneuver easily, pull spreaders, rollers. Convert to snow plow with snow blade.

Design—Trimmer type housing. Heavy gauge steel frame. Draw bar hitch. **Blade**—Austempered steel high lift. **Engine**—4-cycle engine built to rigid AMF specifications. Automotive type differential. Easy-pull recoil starter. **Controls**—Throttle with "choke" and "off" control. 4 speeds forward, neutral and reverse. Blade throw-out lever actuates blade brake, eliminates coasting. **Orbit Disc Power Drive**—Eliminates troublesome gears. **Belt-Driven Blade Quill**—Sealed precision ground radial bearings. **Cutting Heights**—Adjust while mowing. 4 positions, from 1½″ to 4″. **Weight**—Model 1265, 328 lbs.; Model 1262, 303 lbs.

AMFTRAC—Model 1270
24-INCH 5 H.P. Riding Rotary Mower

This new compact with its sporty tractor look is a great buy. Powers up grades with plenty of pep . . . turns on a dime . . . trims close to trees and fences.

Design—Steel channel construction. Hood pivots for access to engine. Pivoted 3-point suspension of front wheels. Tool tote bar on rear. Draw bar hitch. **Blade**—Flexible-tipped, shock-absorbing high tempered steel Flexor Blade.* **Engine**—5 H.P. 4-cycle engine built to rigid AMF specifications. Recoil start on dash. **Controls**—Dash mounted throttle. Front operated clutch and brake pedal. Hand operated blade clutch lever. Automotive type steering wheel. **Transmission**—Gear type, two speeds forward, neutral and reverse. Pivoted front axle, differential rear axle. **Cutting Heights**—Adjustable with single lever from 1¾″ to 3″. **Shipping Weight**—231 lbs.

All AMF/Homko mowers meet all A.S.A. safety standards.

AMF/HOMKO EDGER-TRIMMER
Model 5399 9-INCH 2½ H.P.

Blade—Super-sharp 9″ hardened austempered steel rotary blade. **Engine**—4-cycle engine built to rigid AMF specifications. **Controls**—Stand-up, fingertip control of edging depth, trimming height and blade speed. Blade clutch stops blade without stopping motor. **Weight**—49 lbs.

AMF WESTERN TOOL, INC.
Subsidiary of American Machine & Foundry Co.
Des Moines, Iowa 50302

EXPORTS: AMF INTERNATIONAL
Division of American Machine & Foundry Co.
261 Madison Ave., New York, N.Y. 10016 U.S.A.
Cable: AMMAFOCO—NEW YORK

Made in Des Moines, Iowa, U.S.A.

Printed in U.S.A.